

PULS

DIN-Rail Power Supplies
DIMENSION Products 2008



DIMENSION



DIMENSION Technology

The DIMENSION family of power supplies distinguishes itself from all others due to significant advances in technology and the implementation of a wide variety of technical improvements.

This new generation of power supplies offers impressive features which includes; compact size, powerful, efficient, reliable, durable, highly functional with the ease of integration and operation. The units have the capability of being used worldwide.

Broad Product Offering

PULS offers you everything – low featured units with only the essential functions or a premium product for more demanding applications. There are other units with semi-regulation, buffer modules, DC-UPS's and a large assortment of accessories. Thanks to the wide variety of options, you only pay for the features that your application requires.

Reduced Space Requirement

A vast reduction in power losses along with an ingenious thermal design allows for sizes smaller than ever. The small footprint enables large space reductions, so be creative and take advantage of the new possibilities.

Generous Power Reserves

Power supplies no longer have to be oversized to accommodate peak loads of dynamic current demands. Depending on the series, PULS guarantees a Power Boost of up to 25% or a Bonus Power® of 50%. In many cases, you can rely on the next smaller unit which can save you money.

Integrated Reliability

The same high quality standards apply to all devices. The service life of the electrolytic capacitors that PULS uses is specified according to the manufacturers datasheets which is at least a minimum of 50,000h. The MTBF figure is typically higher than 700,000h and we also provide a 3 year warranty.

DIMENSION Series at a Glance

C-Series

Power supplies for general applications

For users who are looking for power supplies in a compact housing, that are easy to use and offer high reliability. Focussing only on the essential aspects achieves significant price advantages.

Q-Series

Premium class power supplies

Suitable when you need state-of-the-art technology and flexibility for demanding tasks. With outstanding efficiency, 50% Bonus Power and many additional features this series is the „Best in Class“.

X-Series

3-Phase semi-regulated power supplies

The attractive alternative for supplying DC motors and other non-critical loads. Small compromises in the output voltage regulation and ripple voltage allow a cost efficient design with low power losses.

U-Series

Bridging of power outages

Back-up for minutes with a DC-UPS utilising only one 12V battery or for seconds with our battery-free buffer module with no battery wearout. This prevents downtime, loss of data and long restart sequences.



Y-Series

Decoupling modules with diodes

For building redundant power supply systems or to isolate sensitive load circuits with or without alarm signals.

Z-Series

Mounting brackets


For installation into low profile cabinets or for panel installation where there is no DIN-rail available.



Power Supplies and DC/DC-Converters

The C-Series includes all the essential basic functions and the devices have a power reserve of up to 20% (except CS3). This extra current may be used continuously at temperatures up to +45°C (+113°F). In addition to the auto-select input, you can also choose a single input version of 115V or 230V which is sufficient for many applications. This option supports regional applications and offers an additional cost saving without sacrificing functionality.

- 1-Phase input
- 20% Power reserve
- -25°C (13°F) to +60°C (+140°F) without derating



20% Extra output power for dynamic loads, continuous operation is available up to 45°C.



| CD-Series | DC/DC Converters | CD5 | | |
|------------------|------------------|-----------------------|---|-----------------------|
| | | 12V 8A | 24V 5A | 24V 5A |
| DC Input voltage | | DC 24V | DC 24V | DC 48V |
| Range | | 18-32.4Vdc | 18-32.4Vdc | 36-60Vdc |
| Output Voltage | | 12-15V | 23-28V | 23-28V |
| Output Current | continuous | 8-6.4A | 5-4.3A | 5-4.3A |
| Power Reserves | min. | +20% | +20% | +20% |
| Efficiency | typ. | 88.2% | 90.3% | 90.3% |
| Power Losses | typ. | 12.4W | 12.9W | 12.9W |
| Dimensions | WxHxD in mm | 32x124x102 | 32x124x102 | 32x124x117 |
| Order Number | | CD5.121 ⁹⁾ | CD5.241 ⁹⁾ CD5.241-S1 ⁸⁾⁹⁾ | CD5.242 ⁹⁾ |

8) with spring-clamp connection terminals, DC-OK-relay contact and Input-low contact 9) available Q1/2008

| CS-Series | | CS3 | | | CS5 | | | CS10 | | | |
|---------------------------|---------------|------------|---|----------------|------------|---|----------------|------------|-------------|--|--|
| | | 24V 3.3A | 24V 5A | 24V 5A | 24V 5A | 24V 10A | 24V 10A | 24V 10A | 48V 5A | | |
| Output Voltage | | 24-28V | 24-28V | 24-28V | 24-28V | 24-28V | 24-28V | 24-28V | 48-52V | | |
| Output Current | continuous | 3.3-2.7A | 5-4.3A | 5-4.3A | 5-4.3A | 10-8.6A | 10-8.6A | 10-8.6A | 5-4.6A | | |
| Output Power | continuous | 80W | 120W | 120W | 120W | 240W | 240W | 240W | 240W | | |
| Power Reserves | min. | - | +20% | +20% | +20% | +20% | +20% | +20% | +20% | | |
| Efficiency | 120V typ. | 88.0% | 89.4% | 90.0% | - | 91.0% | 91.3% | - | 91.0% | | |
| | 230V typ. | 89.8% | 90.2% | - | 90.2% | 91.6% | - | 91.3% | 91.6% | | |
| Power Losses | 120V typ. | 11.1W | 14.5W | 13.5W | - | 23.7W | 23.4W | - | 23.7W | | |
| | 230V typ. | 9.1W | 13.2W | - | 13.2W | 22.0W | - | 23.4W | 22.0W | | |
| AC Input voltage | | 100-240V | 115/230V | 100-120V | 200-240V | 115/230V | 100-120V | 200-240V | 115/230V | | |
| tolerance | | ±10% | -22%/+15% | ±10% | ±10% | -22%/+15% | ±10% | ±10% | -22%/+15% | | |
| | | Wide Range | Auto Select | - | - | Auto Select | - | - | Auto Select | | |
| Power Factor | 120/230V typ. | 0.61/0.56 | 0.56/0.47 | 0.59/- | -0.5 | 0.59/0.51 | 0.57/- | -0.52 | 0.59/0.51 | | |
| Hold-up Time | 120/230V typ. | 29/120ms | 80/78ms | 80ms/- | -78ms | 46/47ms | 46ms/- | -45ms | 46/47ms | | |
| Inrush Current Limitation | | NTC | active | NTC | NTC | active | NTC | NTC | active | | |
| EN 61000-3-2 (PFC Norm) | | yes | no | not applicable | yes | see 3) | not applicable | no | no | | |
| Dimensions | WxHxD in mm | 32x124x102 | 32x124x117 | 32x124x117 | 32x124x117 | 60x124x117 | 60x124x117 | 60x124x117 | 60x124x117 | | |
| Order Number | | CS3.241 | CS5.241 CS5.241-C1 ²⁾ CS5.241-S1 ¹⁾ | CS5.243 | CS5.244 | CS10.241 CS10.242 ³⁾ CS10.241-S1 ¹⁾ | CS10.243 | CS10.244 | CS10.481 | | |


1) with spring-clamp connection terminals 2) conformal coated PC-board 3) CS10.242 fulfills EN 61000-3-2



Premium Power Supplies

The wide variety of features and an active PFC (QS5 and higher) gives you everything you could want. These high-tech-devices combine 50% power reserves, immunity against mains fluctuations between 60Vac and 300Vac (1-Ph units) with an outstanding efficiency. The uniquely designed spring-clamp terminals are easy to use while offering a reliable and long-lasting connection.

- Wide-range AC input (85-276Vac)⁴⁾
- Wide-range DC input (88-375Vdc)⁴⁾
- 50% Power reserve
- -25°C (13°F) to +60°C (+140°F) without derating
- Lowest inrush current surge⁴⁾
- DC-OK relay contact (except for QS3)
- Active harmonic correction (PFC)
- Quick-connect spring-clamp terminals



| Q-Series | QS3 | | QS5 | | QS10 | | | |
|----------------------------|-----------------|------------|-----------------|------------|-----------------|-----------------|-----------------|-----------------|
| | 24V | 3.4A | 24V | 5A | 24V 10A | 12V 15A | 30V 8A | 48V 5A |
| Output Voltage | 24-28V | | 24-28V | | 24-28V | 12-15V | 28-32V | 48-56V |
| Output Current | continuous | 3.4-3A | 5-4.5A | 10-9A | 15-13.5A | 8.6-7.5A | 5-4.3A | |
| Output Power | continuous | 80W | 120W | 240W | 180W | 240W | 240W | |
| Power Reserves | min. | +50% | +50% | +50% | +50% | +50% | +50% | |
| Efficiency ⁶⁾ | typ. | 90.0% | 92.7% | 93.0% | 91.8% | 93.0% | 92.0% | |
| Power Losses ⁶⁾ | typ. | 9.1W | 9.4W | 18.1W | 16.1W | 18.1W | 20.9W | |
| AC Input voltage | 100-240V | | 100-240V | | 100-240V | 100-240V | 100-240V | 100-240V |
| tolerance | ±15% | | -15%/+10% | | ±15% | ±15% | ±15% | ±15% |
| Power Factor ⁷⁾ | typ. | 0.53/0.47 | 0.99/0.91 | 0.98/0.92 | 0.98/0.92 | 0.98/0.92 | 0.98/0.92 | |
| Hold-up Time ⁷⁾ | typ. | 41/174ms | 34/65ms | 27/28ms | 32/32ms | 22/23ms | 27/28ms | |
| DC Input Voltage | 88-375Vdc | | 88-360Vdc | | 88-375Vdc | 88-375Vdc | 88-375Vdc | 88-375Vdc |
| Dimensions | WxHxD in mm | 32x124x102 | 40x124x117 | 60x124x117 | 60x124x117 | 60x124x117 | 60x124x117 | |
| Order Number | QS3.241 | | QS5.241 | | QS10.241 | QS10.121 | QS10.301 | QS10.481 |

4) except QS20.244 5) see datasheet 6) at 230Vac, 3x400Vac or 600Vdc 7) at 120/230Vac, 3x400/480Vac or 600Vdc

| Q-Series | QS20 | | | | QT20 (3 Ph) | | | QTD20 (DC) | |
|----------------------------|-----------------|-----------------|-----------------|-----------------|-------------------|-------------------|-------------------|-----------------|--------------------------|
| | 24V 20A | 24V 20A | 36V 13A | 48V 10A | 24V 20A | 36V 13A | 48V 10A | 24V 20A | |
| Output Voltage | 24-28V | 24-28V | 36-42V | 48-55V | 24-28V | 36-42V | 48-55V | 24-28V | |
| Output Current | continuous | 20-17A | 20-17A | 13.3-11.4A | 10-8.7A | 20-17.5A | 13.3-11.4A | 10-8.7A | 20-17.5A |
| Output Power | continuous | 480W | 480W | 480W | 480W | 480W | 480W | 480W | |
| Power Reserves | min. | +50% | +50% | +50% | +50% | +50% | +50% | +50% | +25% ⁵⁾ |
| Efficiency ⁶⁾ | typ. | 93.9% | 94.5% | 94.0% | 94.3% | 95.0% | 94.8% | 95.4% | 95.0% |
| Power Losses ⁶⁾ | typ. | 31.4W | 28.3W | 30.6W | 29.0W | 25.3W | 26.3W | 23.1W | 25.2W |
| AC Input voltage | 100-240V | 200-240V | 100-240V | 100-240V | 3x380-480V | 3x380-480V | 3x380-480V | - | |
| tolerance | ±15% | | ±15% | | ±15% | | | - | |
| Power Factor ⁷⁾ | typ. | 0.95/0.9 | - /0.5 | 0.95/0.9 | 0.95/0.9 | 0.94 | 0.94 | 0.94 | - |
| Hold-up Time ⁷⁾ | typ. | 32/51ms | - /46ms | 32/51ms | 32/51ms | 22ms | 22ms | 22ms | 22ms |
| DC Input Voltage | 88-375Vdc | | - | 88-375Vdc | 88-375Vdc | use QTD20.241 | - | - | 360-900Vdc ⁵⁾ |
| Dimensions | WxHxD in mm | 82x124x117 | 70x124x127 | 82x124x127 | 82x124x127 | 65x124x127 | 65x124x127 | 65x124x127 | 65x124x127 |
| Order Number | QS20.241 | | QS20.244 | QS20.361 | QS20.481 | QT20.241 | QT20.361 | QT20.481 | QTD20.241 |

4) except QS20.244 5) see datasheet 6) at 230Vac, 3x400Vac or 600Vdc 7) at 120/230Vac, 3x400/480Vac or 600Vdc


DC-UPS

During black-outs of the mains voltage, the DC-UPS delivers with the help of a battery, the DC load current without any interruptions. A unique feature of this system is that only one 12V battery is required, as the UPS module boosts the 12V to a 24V level. This saves space and makes paired batteries unnecessary. Another unique feature is the stabilised output voltage in buffer mode, which has no declining voltage characteristic as with many other DC-UPS systems. The UBC-Series is very compact due to the integrated battery. The UB10-Series is flexible in choosing battery sizes, since the battery is connected as an external module.



| UB-Series | | UB10 24V 10A | UBC10 24V 10A |
|-----------------------|---------------------|--|------------------|
| Battery | | extern | intern (5Ah) |
| Voltage Range | | 24-28V | 24-28V |
| Output Current | Normal Mode | 15A | 15A |
| | Buffer Mode | 10A (15A for 5s) | 10A (15A for 5s) |
| Input Current | Charging Mode | typ. 1.1A | typ. 1.1A |
| Allowed Battery Sizes | | 3.9-27Ah (12V) | - |
| Dimensions | WxHxD in mm | 49x124x117 | 123x124x119 |
| Order Number | DC-UPS | UB10.241 UB10.245¹⁰⁾ | UBC10.241 |
| Battery Modules | 12V 7Ah 12V 26Ah | UZK12.071 UZK12.261 | |

10) with an additional 12V output



Typical back-up time

Buffer Modules

The buffer units are supplementary devices that bridge the gap of short power interruptions. When the power supply provides a suitable voltage, the capacitors of the buffer unit will be charged. When there is a voltage failure, this stored energy is released in a regulated process to the load. The buffer modules are simply connected with two lines parallel to the load circuit. Thanks to the utilised electrolytic capacitors, the buffer units are maintenance-free and can be used even at ambient temperatures up to +70°C.


| UF-Series | | 24V 20A | UF20 48V 20A |
|----------------------|-------------|-----------------|-----------------|
| Voltage Range | | 24-28V | 48-56V |
| Buffer Current | | 20A | 20A |
| Charging Time | typ. | 18s | 21s |
| Buffer Current | min. | 200ms at 20A | 100ms at 20A |
| | typ. | 310ms at 20A | 150ms at 20A |
| | typ. | 43s at 0.1A | 21s at 0.1A |
| | typ. | | |
| Dimensions | WxHxD in mm | 64x124x102 | 64x124x102 |
| Order Number | | UF20.241 | UF20.481 |

3-Phase Semi-Regulated Power Supplies


Power supplies in the Dimension X-Series include a new and innovative concept for generating a DC voltage from a three phase input. The X-Series is the ideal power supply for drive systems, DC motors, heaters and valves that do not require very high degree of regulation on the output voltage. These devices do not achieve the precision of a fully regulated switched-mode power supply but they are significantly better in output voltage regulation than transformer power supplies. These units are lightweight at only 1.4kg (3lb.) and deliver 960W of constant power and an additional 25% extra power for dynamic loads. In an overload condition the unit switches off after a certain period of time to protect the system.

| X-Series | 3-Ph | XT40 | | | |
|------------------------|-------------|-----------------|-----------------|-----------------|-----------------|
| | | 24V 40A | 36V 26A | 48V 20A | 72V 13A |
| Output Voltage | | 24V | 36V | 48V | 72V |
| Output Current | contin. | 40A | 26.6A | 20A | 13.3A |
| | up to 15s | 50A | 33.3A | 25A | 16.7A |
| Ripple & Noise | max. | 1.5Vpp | 2Vpp | 2.5Vpp | 3Vpp |
| Efficiency | typ. | 95.5% | 95.5% | 96.0% | 95.5% |
| Power Losses | typ. | 45.2W | 45.2W | 40.0W | 45.2W |
| Dimensions | WxHxD in mm | 96x124x157 | | | |
| 3x 400V Version | | XT40.241 | XT40.361 | XT40.481 | XT40.721 |
| 3x 480V Version | | XT40.242 | XT40.362 | XT40.482 | XT40.722 |

- 3-Phase input
- Alternative to 50Hz transformers
- 25% Power reserve
- -25°C (-13°F) to +60°C (+140°F) without derating
- No inrush current surge
- Efficiency up to 96%
- Shutdown in case of overload
- Simple diagnostics



Regulation of output voltage



Power reserves and overload behaviour


Y Diode- and Redundancy Modules

| Y-Series | Diode | YRM2 | |
|----------------------|-------------|------------------|-------------------|
| | | 2x10A | 2x10A |
| Voltage Range | | 10-60V | 24-60V |
| Number of Inputs | | 2 | 2 |
| Number of Outputs | | 1 | 1 |
| Output Current | max. | 25A | 25A |
| Alarm Signal | | - | relay contacts |
| Alarm Threshold | | - | 21.5V |
| Connection Terminals | | spring terminals | screw terminals |
| Dimensions | WxHxD in mm | 32x124x102 | 32x124x117 |
| Order Number | | YR2.DIODE | YRM2.DIODE |

Z Accessories

| | Wall/Panel Mount Bracket |
|------------------|------------------------------|
| ZM1.WALL | for C-, Q-, U-, Y-Series |
| | Side Mount Bracket |
| ZM11.SIDE | for CS3, CS5, QS3, YR2, YRM2 |
| ZM12.SIDE | for QS5 |
| ZM13.SIDE | for CS10, QS10 |
| ZM14.SIDE | for QT20, QTD20, UF20 |
| ZM15.SIDE | for QS20 ⁴⁾ |

4) except QS20.244



Success with Innovation and Quality

Everything starts with an idea! PULS is the only organisation solely focussed on DIN-Rail power supplies which allows Bernhard Erdl and his experienced team to develop premium pioneer products. The outstanding performance of the SilverLine and MiniLine families of products has quickly made them a market standard and the DIMENSION series is poised to extend this success. In 2006 the innovative performance of PULS' new line was honoured with the prestigious Frost & Sullivan Technology Leadership Award.

DIMENSION products are unusually compact and many features were specifically developed with long service life and high reliability in mind. The compactness of the unit creates additional space, giving end users more design freedom. A well thought-out design with many unique strengths gives the DIMENSION its lead, making it a valuable component and not restricted just to technology oriented systems integrators and suppliers.

We manufacture the products with very high quality standards in our own factories in the Czech Republic. The first of these factories was opened in 1998; in 2007 an innovated modern building was added. As many of our customers are increasingly using foreign operations to manufacture their products, PULS has established subsidiaries in the key economic regions of the world to provide local service and distribution.

Germany PULS in Munich
Tel. +49 89 9278 0 www.pulspower.com

China PULS in Shanghai
Tel. +86 512 62881820 www.pulspower.cn

France PULS in Limonest/Lyon
Tél. +33 608 5494 60 www.puls-power.fr

North America PULS in St. Charles/Chicago
Tel. +1 630 587 9780 www.pulspower.com/us

Austria PULS in Rohrbach
Tel. +43 2764 32 13 www.pulspower.com

Switzerland PULS in Oberflachs/Aargau
Tel. +41 56 450 18 10 www.puls-power.ch

United Kingdom PULS in Bedfordshire
Tel. +44 845 130 1080 www.puls.co.uk

You can find all the PULS worldwide distributors on our website:

www.pulspower.com

The information presented in this document is believed to be accurate and reliable and may change without notice.